



Male Crimp Contacts

These male crimp contacts are available in 10 Amp and 16 Amp versions. The 10 Amp crimp contacts are suitable for conductor size up to 2.5 sq.mm.and the 16 Amp crimp contact are suitable for conductor size up to 4 sq.mm to be used along with male contact careers.

Technical Data

Material	Turned / Machined Copper Alloy
Surface Material	Hard Silver Hard Gold on request
Current Capacity	10 A, 16 A & 40 A

Accessories

Image	Cat. no.	Description
	Crimping Tools	Crimping tools are the basic instruments that are used to...

Ordering Information

Male Crimp Contacts - Turned

Cat. No.	Wire Size sq.mm	Current Capacity Amp	Stripping Length	Standard Pack (Pieces)
WMCT0.5/10A	0.5	10	8	100
WMCT0.75/10A	0.75	10	8	100
WMCT1.0/10A	1	10	8	100
WMCT1.5/10A	1.5	10	8	100
WMCT2.5/10A	2.5	10	6	100
WMCT0.37/16A	0.37	16	7.5	50
WMCT0.5/16A	0.5	16	7.5	50
WMCT0.75/16A	0.75	16	7.5	50
WMCT1.0/16A	1	16	7.5	50
WMCT1.5/16A	1.5	16	7.5	50
WMCT2.5/16A	2.5	16	7.5	50
WMCT4.0/16A	4	16	7.5	50
WMCT6.0/40A	4	40	9.6	100