



These connectors are used to clamp flexible corrugated conduits. They offer IP67 protection and are available in Pg and Metric threads. The 45° configuration enables angular conduit entry into the panel or equipment.

Technical Details :	
Material	Polyamide 6
Colour	RAL 7001 (Grey) RAL 9005 (Black)
Temperature Range	-40° C to +105° C Continuous, +150° C Short Term
Protection Class	IP 67
Threads available	Pg, Metric and NPT
Approvals	CE

### 45° ANGULAR CONNECTORS



#### Pg Thread

Size	Suitable for Conduit Size	Cat. No. Grey	Cat. No. Black	Thread Diameter (mm)	Thread Length (mm)	Standard Pack (pieces)
Pg 9	10	TAC-P09G	TAC-P09B	15.2	13	50
Pg 11	12	TAC-P11G	TAC-P11B	18.6	13	30
Pg 13.5	16	TAC-P136G	TAC-P136B	20.4	13	30
Pg 16	16	TAC-P16G	TAC-P16B	22.5	13	30
Pg 21	22	TAC-P21G	TAC-P21B	28.3	15	30
Pg 29	28	TAC-P29G	TAC-P29B	37.0	15	10
Pg 36	36	TAC-P36G	TAC-P36B	47.0	20	10
Pg 48	48	TAC-P48G	TAC-P48B	59.3	20	5

#### Metric Thread

Size	Suitable for Conduit Size	Cat. No. Grey	Cat. No. Black	Thread Diameter (mm)	Thread Length (mm)	Standard Pack (pieces)
M 12 x 1.5	10	TAC-M10G	TAC-M10B	12.0	13	50
M 16 x 1.5	12	TAC-M12G	TAC-M12B	16.0	13	30
M 20 x 1.5	16	TAC-M16G	TAC-M16B	20.0	13	30
M 25 x 1.5	22	TAC-M22G	TAC-M22B	25.0	15	30
M 32 x 1.5	28	TAC-M28G	TAC-M28B	32.0	15	10
M 40 x 1.5	36	TAC-M36G	TAC-M36B	40.0	20	10
M 50 x 1.5	48	TAC-M48G	TAC-M48B	50.0	20	5

#### PF Thread

Size	Suitable for Conduit Size	Cat. No. Grey	Cat. No. Black	Thread Diameter (mm)	Thread Length (mm)	Standard Pack (pieces)
G 1/2"	10	TAC-G10G	TAC-G10B	20.9	13	50
G 1/2"	12	TAC-G12G	TAC-G12B	20.9	13	30
G 1/2"	16	TAC-G16G	TAC-G16B	20.9	13	30
G 3/4"	22	TAC-G22G	TAC-G22B	26.4	15	30
G 1"	28	TAC-G28G	TAC-G28B	33.2	15	10
G 1 1/4"	36	TAC-G36G	TAC-G36B	41.9	20	10
G 2"	48	TAC-G48G	TAC-G48B	59.6	20	5