


90° ELBOW FLANGE CONNECTORS



These connectors are used to clamp flexible corrugated conduits. They offer IP67 protection. These connectors are available with mounting holes for fixing on the panel or equipment surface. The 90° configuration enables perpendicular conduit entry into the panel or equipment.

Technical Details :	
Material	Polyamide 6
Colour	RAL 7001 (Grey) RAL 9005 (Black)
Temperature Range	-40° C to +105° C Continuous, +150° C Short Term
Protection Class	IP 67




Suitable for Conduit Size	Cat. No. Grey	Cat. No. Black	E (mm)	F (mm)	G (mm)	H (mm)	I (mm)	Standard Pack (pieces)
12	TWOC-12G	TWOC-12B	-	36.5	5.5	45	32	50
16	TWOC-16G	TWOC-16B	-	36.5	5.5	45	32	30
22	TWOC-22G	TWOC-22B	30.5	53.5	5.5	66.5	45	20
28	TWOC-28G	TWOC-28B	30.5	53.5	6	66.5	45	10
36	TWOC-36G	TWOC-36B	30.5	72.5	7	85.5	64	10
48	TWOC-48G	TWOC-48B	30.5	72.5	7	85.5	78	10

90° ELBOW FLANGE CONNECTORS



These connectors are used to clamp flexible corrugated conduits. They offer IP67 protection. These connectors are available with mounting holes for fixing on the panel or equipment surface. The 90° configuration enables perpendicular conduit entry into the panel or equipment.

Technical Details :	
Material	Polyamide 6
Colour	RAL 7001 (Grey) RAL 9005 (Black)
Temperature Range	-40° C to +105° C Continuous, +150° C Short Term
Protection Class	IP 67



Suitable for Conduit Size	Cat. No. Grey	Cat. No. Black	E (mm)	F (mm)	G (mm)	H (mm)	I (mm)	Standard Pack (pieces)
56	TWOC-56G	TWOC-56B	67	61	7	97	81	10
70	TWOC-70G	TWOC-70B	84	78	7	113	98	10
95	TWOC-95G	TWOC-95B	108	94	8	146	125	10