



These special connectors are used to clamp flexible corrugated conduits. They offer IP67 protection and are available in Pg and UNEF threads. These connectors also act as a cable gland for the cable going through the conduit.



CONNECTORS TO SECURE

CABLES AND CONDUITS

Technical Details :	
Material	Polyamide 6
Colour	RAL 7001 (Grey) RAL 9005 (Black)
Temperature Range	-40° C to +105° C Continuous, +150° C Short Term
Protection Class	IP 67
Threads available	Pg, Metric & G - Male Thread*, UNEF - Female Thread

Pg Male Thread

Size	Suitable for Conduit Size	Cat. No. Grey	Cat. No. Black	Thread Length (mm)	Clamping Range (mm)	Standard Pack (pieces)
Pg 7	10	TNCC-P07NG	TNCC-P07B	15	3.5 - 6.5	50
Pg 9	10	TNCC-P09NG	TNCC-P09B	15	3.5 - 6.5	50
Pg 11	12	TNCC-P11NG	TNCC-P11B	15	4 - 8	30
Pg 13.5	12	TNCC-P132NG	TNCC-P132B	15	4 - 8	30
Pg 13.5	16	TNCC-P13NG	TNCC-P13B	15	7 - 12	30
Pg 16	16	TNCC-P16NG	TNCC-P16B	15	7 - 12	30
Pg 21	22	TNCC-P21NG	TNCC-P21B	15	12 - 18	30
Pg 29	28	TNCC-P29NG	TNCC-P29B	15	18 - 26	15
Pg 36	36	TNCC-P36NG	TNCC-P36B	19	22 - 33	15
Pg 48	48	TNCC-P48NG	TNCC-P48B	19	30 - 38	10

* Metric & G Male Thread Connectors available on request.

UNEF Female Thread

UNEF Thread Size	Suitable for Conduit Size	Cat. No. Grey	Cat. No. Black	Inner Thread Length (mm)	Cable Clamping Range (mm)	Standard Pack (pieces)
1/2-28	10	TICC-U1010NG	TICC-U1010B	13	3.5-6.5	50
5/8-24	10	TICC-U1210NG	TICC-U1210B	13	3.5-6.5	30
3/4-20	10	TICC-U1410NG	TICC-U1410B	13	3.5-6.5	30
5/8-24	12	TICC-U1212NG	TICC-U1212B	13	4-8	30
3/4-20	12	TICC-U1412NG	TICC-U1412B	13	4-8	30
1-20	12	TICC-U1812NG	TICC-U1812B	13	4-8	30
7/8-20	16	TICC-U1616NG	TICC-U1616B	13	7-12	30
1-20	16	TICC-U1816NG	TICC-U1816B	13	7-12	30
1 3/16-18	16	TICC-U2016NG	TICC-U2016B	13	7-12	30
1 7/16-18	16	TICC-U2816NG	TICC-U2816B	15	7-12	30
1 3/16-18	22	TICC-U2222NG	TICC-U2222B	15	12-16	30
1 7/16-18	22	TICC-U2822NG	TICC-U2822B	15	12-16	30
1 7/16-18	28	TICC-U2828NG	TICC-U2828B	15	18-26	20
1 3/4-18	28	TICC-U3228NG	TICC-U3228B	15	18-26	10
2-18	28	TICC-U3628NG	TICC-U3628B	15	18-26	10
2-18	36	TICC-U3636NG	TICC-U3636B	19	22-33	10