

**STC****SYC**

Y &amp; T CONDUIT COUPLERS

WITH CLAMP LOCKS



These manifolds are used to join two or three flexible Conduits of the same size or of different sizes with outside gripping. They are available in Straight, Elbow, 'T' and 'Y' shapes.

Technical Details :	
Material	Polyamide 66 (PA)
Protection Class	RAL 9005 (Black)
Temperature Range	-40° C to +135° C Continuous, +150° C Short Term

### Y & T Conduit Couplers

Cat. No.	Suitable for Conduit Size			Standard Pack (pieces)
	A	B	C	
SYC070404	07	04	04	50
SYC070707	07	07	07	50
SYC101010	10	10	10	50
SYC121010	12	10	10	50
SYC121210	12	12	10	50
SYC161010	16	10	10	50
SYC161210	16	12	10	50
SYC161212	16	12	12	50
SYC161610	16	16	10	50
SYC161612	16	16	12	50
SYC221616	22	16	16	50
SYC222216	22	22	16	50
STC070707	07	07	07	50
STC100707	10	07	07	50
STC101010	10	10	10	50
STC120712	12	07	12	50
STC121010	12	10	10	50
STC121210	12	12	10	50
STC121212	12	12	12	50
STC161010	16	10	10	50
STC161012	16	10	12	50
STC160716	16	07	16	50
STC161016	16	10	16	50
STC161212	16	12	12	50
STC161216	16	12	16	50
STC161612	16	16	12	50
STC161616	16	16	16	50
STC162216	16	22	16	50
STC221022	22	10	22	50
STC221216	22	12	16	50
STC221612	22	16	12	50
STC221222	22	12	22	50
STC222216	22	22	16	50



These manifolds are used to join two or three flexible Conduits of the same size or of different sizes with outside gripping. They are available in Straight, Elbow, 'T' and 'Y' shapes.

Technical Details :	
Material	Polyamide 66 (PA)
Protection Class	RAL 9005 (Black)
Temperature Range	-40 <sup>o</sup> C to +135 <sup>o</sup> C Continuous, +150 <sup>o</sup> C Short Term

CONDUIT COUPLERS WITH CLAMP

LOCKS - STRAIGHT & ELBOW



### Straight & Elbow Conduit Coupler

Cat. No.	Suitable for Conduit Size		Standard Pack (pieces)
	A	B	
SSC0707	07	07	50
SSC1007	10	07	50
SSC1010	10	10	50
SSC1210	12	10	50
SSC1212	12	12	50
SSC1612	16	12	50
SSC1616	16	16	50
SEC1010	10	10	50
SEC1212	12	12	50
SEC1616	16	16	50