



These hoods are suitable for conductors which run parallel to the surface on which the appropriate hood and housing are mounted. The spring loaded double locking system ensures a perfect mating between the male and the female inserts even if accidentally one of the locks opens up.

Technical Details :	
Material	Die cast Alluminium alloy
Protection Class	IP 65
Voltage	For Inserts upto 500V
Thread	Pg, Metric
Gasket	Vinyl Nitrile Elastomer (NBR)

HOODS - DOUBLE LOCK

(SIDE ENTRY)



Cat. No.	Enclosure Type	Enclosure Size (mm)	Cable Gland Size
W10CS2P16/B10	10B	57 x 27	Pg 16
W16CS2P21/B16	16B	77 x 27	Pg 21
W16CS2M25/B16	16B	77 x 27	M 25 x 1.5
W24CS2P21/B24	24B	104 x 27	Pg 21
W24CS2P29/B24	24B	104 x 27	Pg 29
W24CS2M32/B24	24B	104 x 27	M 32 x 1.5
W32HCS2P21/A32	32A	66 x 40	Pg 21
W32HCS2M32/A32	32A	66 x 40	M 32 x 1.5
W32HCS2P29/B32	32B	77 x 62	Pg 29
W32HCS2P36/B32	32B	77 x 62	Pg 36