



HOODS - SINGLE LOCK

(SIDE ENTRY)



These hoods are suitable for conductors which run parallel to the surface on which the appropriate hood and housing are mounted. The spring loaded single locking system ensures a perfect mating between the male and the female inserts while providing them with IP 65 protection.

Technical Details :	
Material	Die cast Aluminium alloy
Protection Class	IP 65
Voltage	For Inserts upto 500V
Thread	Pg, Metric
Gasket	Vinyl Nitrile Elastomer (NBR)

Cat. No.	Enclosure Type	Enclosure Size (mm)	Cable Gland Size
W06CS1P13/B6	6B	44 x 27	Pg 13.5
W06CS1P16/B6	6B	44 x 27	Pg 16
W06CS1M20/B6	6B	44 x 27	M 20 x 1.5
W10CS1P16/A10	10A	49 x 16	Pg 16
W10CS1M20/A10	10A	49 x 16	M 20 x 1.5
W10CS1P16/B10	10B	57 x 27	Pg 16
W10CS1M25/B10	10B	57 x 27	M 25 x 1.5
W16CS1P16/A16	16A	66 x 16	Pg 16
W16CS1M20/A16	16A	66 x 16	M 20 x 1.5
W16CS1P21/B16	16B	77 x 27	Pg 21
W16CS1M25/B16	16B	77 x 27	M 25 x 1.5
W24CS1P21/B24	24B	104 x 27	Pg 21
W24CS1M32/B24	24B	104 x 27	M 32 x 1.5
W32HCS1P36/B32	32B	77 x 62	Pg 36
W48HCS1P29/B48	48B	104 x 62	Pg 29
W48CS1P36/B48	48B	104 x 62	Pg 36
W48HCS1M50/B48	48B	104 x 62	M 50 x 1.5