



These male and female crimp contacts are available in 10 Amp and 16 Amp versions. The 10 Amp crimp contacts are suitable for conductor size upto 2.5 sq.mm. and the 16 Amp crimp contact are suitable for conductor size upto 4 sq.mm.

#### Female Crimp Contacts



10A

16A

#### Male Crimp Contacts



10A

16A

MALE & FEMALE CRIMP CONTACTS

FOR CONTACT CARRIERS

Technical Details :	
Material	Turned / Machined Copper Alloy
Surface Material	Hard Silver
Current Capacity	10 A and 16 A

#### Female Crimp Contacts

Cat. No.	Current Capacity Amp	Wire Size in sq.mm	Dia A / No. of Grooves	Stripping Length mm
WFCT0.37/10A	10	0.14 - 0.37	0.90 mm	8
WFCT0.5/10A	10	0.5	1.10 mm	8
WFCT0.75/10A	10	0.75	1.30 mm	8
WFCT1.0/10A	10	1.0	1.45 mm	8
WFCT1.5/10A	10	1.5	1.75 mm	8
WFCT2.5/10A	10	2.5	2.25 mm	6
WFCT0.37/16A	16	0.14 - 0.37	0 No.	7.5
WFCT0.5/16A	16	0.5	0 No.	7.5
WFCT0.75/16A	16	0.75	1 No.	7.5
WFCT1.0/16A	16	1.0	1 No.	7.5
WFCT1.5/16A	16	1.5	2 No.	7.5
WFCT2.5/16A	16	2.5	3	7.5
WFCT3.0/16A	16	3.0	1 Wide No.	7.5
WFCT4.0/16A	16	4.0	0 No.	7.5

#### Male Crimp Contacts

Cat. No.	Current Capacity Amp	Wire Size in sq.mm	Dia A / No. of Grooves	Stripping Length mm
WMCT0.37/10A	10	0.14 - 0.37	0.90 mm	8
WMCT0.5/10A	10	0.5	1.10 mm	8
WMCT0.75/10A	10	0.75	1.30 mm	8
WMCT1.0/10A	10	1.0	1.45 mm	8
WMCT1.5/10A	10	1.5	1.75 mm	8
WMCT2.5/10A	10	2.5	2.25 mm	6
WMCT0.37/16A	16	0.14 - 0.37	0 No.	7.5
WMCT0.5/16A	16	0.5	0 No.	7.5
WMCT0.75/16A	16	0.75	1 No.	7.5
WMCT1.0/16A	16	1.0	1 No.	7.5
WMCT1.5/16A	16	1.5	2 No.	7.5
WMCT2.5/16A	16	2.5	3 No.	7.5
WMCT3.0/16A	16	3.0	1 Wide No.	7.5
WMCT4.0/16A	16	4.0	0 No.	7.5