



These inserts are used in applications where sealing and strain relief protection is required for multiple cables passing through a single cable gland.

Technical Details :	
Material	Perbunan (NBR)
Colour	RAL 9005 (Black)
Threads available	For Pg, Metric and NPT threaded Cable Glands

### MULTI-HOLE SEALING INSERTS



For Cable Gland Size	Cat. No.	Number of Holes	Diameter of Hole (mm)	Standard Pack (pieces)
Pg 7 / M 12 (3 - 6.5)	BMS-01A	2	1	50
Pg 9 / M 16 (4 - 8)	BMS-02A	2	3	50
Pg 9 / M 16 (4 - 8)	BMS-02B	3	2	50
Pg 9 / M 16 (4 - 8)	BMS-02C	4	2	50
Pg 9 / M 16 (4 - 8)	BMS-02D	4	3	50
Pg 9 / M 16 (4 - 8)	BMS-02E	2	4	50
Pg 11 / M 16 (5 - 10)	BMS-03A	2	4	50
Pg 11 / M 16 (5 - 10)	BMS-03B	2	4.5	50
Pg 11 / M 16 (5 - 10)	BMS-03C	3	4	50
Pg 11 / M 16 (5 - 10)	BMS-03D	3	5	50
Pg 11 / M 16 (5 - 10)	BMS-03E	4	3.5	50
Pg 13.5 / M 20 (6 - 12)	BMS-04A	2	6	50
Pg 13.5 / M 20 (6 - 12)	BMS-04B	3	4	50
Pg 13.5 / M 20 (6 - 12)	BMS-04C	3	5	50
Pg 16 / M 20 (10 - 14)	BMS-05A	2	4	50
Pg 16 / M 20 (10 - 14)	BMS-05B	2	7	50
Pg 16 / M 20 (10 - 14)	BMS-05C	3	4	50
Pg 16 / M 20 (10 - 14)	BMS-05D	3	6	50
Pg 16 / M 20 (10 - 14)	BMS-05E	4	6	50
Pg 21 / M 25 (11 - 17)	BMS-06	2	8	50
Pg 21 / M 25 (13 - 18)	BMS-06A	2	7	50
Pg 21 / M 25 (13 - 18)	BMS-06B	2	8	50
Pg 21 / M 25 (13 - 18)	BMS-06C	2	9	50
Pg 21 / M 25 (13 - 18)	BMS-06D	3	7	50
Pg 21 / M 25 (13 - 18)	BMS-06E	4	7	50
Pg 29 / M 32 (18 - 25)	BMS-07A	3	8.5	50
Pg 29 / M 32 (18 - 25)	BMS-07B	5	8.5	50
Pg 29 / M 32 (18 - 25)	BMS-07C	8	5	50
Pg 29 / M 32 (18 - 25)	BMS-07D	2	10.5 & 12	50
Pg 29 / M 32 (18 - 25)	BMS-07E	9	4	50
Pg 29 / M 32 (18 - 25)	BMS-07F	6	7.5	50
Pg 29 / M 32 (18 - 25)	BMS-07G	2	8	50
Pg 36 / M 40 (22 - 32)	BMS-08A	6	10	50