Y & T Conduit Couplers With Clamp Locks

These manifolds are used to join two or three flexible Conduits of the same size or of different sizes with inside or outside gripping. They are available in Straight, Elbow, 'T' and 'Y' shapes.

Technical Data

Material	|	Polyamide 66 (PA)
Colour	|	RAL 9005 Black
Temperature Range	|	-40° C to +135° C Continuous, +150° C Short Term

Ordering Information

Y & T Conduit Couplers

Cat. No.	Proximity Sensor Size	Suitable for Conduit OD A Ø mm	Suitable for Conduit OD B Ø mm	Suitable for Conduit OD C Ø mm	Standard Pack (Pieces)
SYC070404	OUTSIDE	10	7.1	7.1	50
SYC070707	OUTSIDE	10	10	10	50
SYC101010	INSIDE	13	13	13	50
SYC121010	INSIDE	15.8	13	13	50
SYC121210	INSIDE	15.8	15.8	13	50
SYC161010	INSIDE	21.2	13	13	50
SYC161210	INSIDE	21.2	15.8	13	50
SYC161212	INSIDE	21.2	15.8	15.8	50
SYC161610	INSIDE	21.2	21.2	13	50
SYC161612	INSIDE	21.2	21.2	15.8	50
SYC221616	INSIDE	25.4	21.2	21.2	50
SYC222216	INSIDE	25.4	25.4	21.2	50
SYC222222	INSIDE	25.4	25.4	25.4	50
STC070707	OUTSIDE	10	10	10	50
STC100707	OUTSIDE	13	10	10	50
STC100810	OUTSIDE	13	11.7	13	50
STC101007	OUTSIDE	13	13	10	50
STC101010	OUTSIDE	13	13	13	50
STC120810	OUTSIDE	15.8	11.7	13	50
STC120712	OUTSIDE	15.8	10	15.8	50
STC120812	OUTSIDE	15.8	11.7	15.8	50
STC121007	OUTSIDE	15.8	13	10	50
STC121010	OUTSIDE	15.8	13	13	50
STC121012	OUTSIDE	15.8	13	15.8	50
STC121207	OUTSIDE	15.8	15.8	10	50
STC121210	OUTSIDE	15.8	15.8	13	50
STC121212	OUTSIDE	15.8	15.8	13	50
STC161012	OUTSIDE	21.2	13	15.8	50
STC160712	OUTSIDE	21.2	10	15.8	50
STC160716	OUTSIDE	21.2	10	21.2	50
STC160816	OUTSIDE	21.2	11.7	21.2	50
STC161016	OUTSIDE	21.2	13	21.2	50
STC161212	OUTSIDE	21.2	15.8	15.8	50
STC161216	OUTSIDE	21.2	15.8	21.2	50

CONTROLWELL INDIA PVT.LTD | D7,Phase 2, M.I.D.C., Dombivli (E), Maharashtra, India-421204
Tel.: +91 251 7120 600 / 6762 600 | Fax: +91 251 7120 700 | Email: connect@connectwell.com

Y & T Conduit Couplers

Cat. No.	Proximity Sensor Size	Suitable for Conduit OD A Ø mm	Suitable for Conduit OD B Ø mm	Suitable for Conduit OD C Ø mm	Standard Pack (Pieces)
STC161607	OUTSIDE	21.2	21.2	10	50
STC161612	OUTSIDE	21.2	21.2	15.8	50
STC161616	INSIDE	21.2	21.2	21.2	50
STC162216	OUTSIDE	21.2	25.4	21.2	50
STC220822	OUTSIDE	25.4	11.7	25.4	50
STC221022	OUTSIDE	25.4	13	25.4	50
STC221212	OUTSIDE	25.4	15.8	15.8	50
STC221216	OUTSIDE	25.4	15.8	21.2	50
STC221612	OUTSIDE	25.4	21.2	15.8	50
STC221222	OUTSIDE	25.4	15.8	25.4	50
STC222216	OUTSIDE	25.4	21.2	21.2	50
STC222222	OUTSIDE	25.4	25.4	25.4	50

CONTROLWELL INDIA PVT.LTD | D7,Phase 2, M.I.D.C., Dombivli (E), Maharashtra, India-421204
Tel.: +91 251 7120 600 / 6762 600 | Fax: +91 251 7120 700 | Email: connect@connectwell.com