



COMPACT SQUARE TYPE

MALE INSERTS



Suitable for 3 A type enclosure with a size of 21 x 21 these inserts provide for the most compact connections and are available from 3 to 12 poles.

| Technical Details : | |
|---------------------|----------------------------|
| Insulation Material | Polycarbonate |
| Contact Material | Silver-Plated Copper Alloy |
| Flammability | UL 94 V0 |
| Temperature Range | -40° C to +125° C |
| Approvals | UL CE |

Male Inserts

| Cat. No. Male Insert | No. of Poles | Current Rating Amp | Voltage Rating Volt | Wire Size sq.mm | Terminal Type |
|-------------------------|--------------|-----------------------|------------------------|--------------------|------------------|
| W03MT/10A3 | 3 + ⊕ | 10 | 230 | 0.5 - 2.5 | Screw |
| W04MT/10A3 | 4 + ⊕ | 10 | 230 | 0.5 - 2.5 | Screw |
| W05MCC/10A3 | 5 + ⊕ | 16 | 250 | 0.5 - 2.5 | Crimp Contact |
| W07MCC/10A3 | 7 + ⊕ | 10 | 250 | 0.14 - 2.5 | Crimp Contact |
| W08MCC/10A3 | 8 | 10 | 50 | 0.14 - 2.5 | Crimp Contact |
| W12MCC/10A3 | 12 + ⊕ | 10 | 400 | 0.5 - 2.5 | Crimp Contact |