



The Helical Corrugated Flame retardant PVC sheathed metal conduits are highly flexible. They do not contain silicon or cadmium. Their robust construction makes them resistant to high mechanical stresses. These also have high impact resistance. These conduits offer IP67 protection when combined with appropriate Controlwell conduit glands.

Technical Details :	
Material	PVC coated Galvanised Steel
Protection Class	IP67
Temperature Range	-25 <sup>o</sup> to +100 <sup>o</sup> C Continuous

Size	Cat. No	Inner Diameter (mm)	Outer Diameter (mm)	Bending Radius R (mm)	Standard Pack (meters)
NW-7	MSP-7	7.0	10.0	25.0	50
NW-9	MSP-9	10.0	14.0	35.0	50
NW-11	MSP-11	13.0	17.0	50.0	50
NW-13.5	MSP-13	15.0	19.0	55.0	50
NW-16	MSP-16	17.0	21.0	60.0	50
NW-21	MSP-21	21.0	27.0	65.0	25
NW-29	MSP-29	28.0	36.0	75.0	25
NW-36	MSP-36	37.0	45.0	90.0	25
NW-42	MSP-42	44.0	52.0	120.0	25
NW-48	MSP-48	48.0	56.0	135.0	25

GALVANISED STEEL FLEXIBLE

CONDUITS - PVC SHEATHED