






STRAIGHT CONNECTORS (Pg & PF THREAD)



These connectors are used to clamp flexible corrugated conduits. They offer IP67 protection and are available in Pg, Metric, PF and NPT threads.

Technical Details :	
Material	Polyamide 6
Colour	RAL 7001 (Grey) RAL 9005 (Black)
Temperature Range	-40°C to +105°C Continuous, +150°C Short Term
Protection Class	IP 67
Threads available	Pg & PF
Approvals	  

Pg Thread

Size	Suitable for Conduit Size	Cat. No. Grey	Cat. No. Black	Thread Diameter (mm)	Thread Length (mm)	Standard Pack (pieces)
Pg 7	7	TNC-P077NG	TNC-P077B	12.5	11	50
Pg 7	10	TNC-P070NG	TNC-P070B	12.5	13	50
Pg 9	7	TNC-P097NG	TNC-P097B	15.2	13	50
Pg 9	10	TNC-P09NG	TNC-P09B	15.2	13	50
Pg 9	12	TNC-P0912NG	TNC-P0912B	15.2	13	50
Pg 11	7	TNC-P117NG	TNC-P117B	18.6	13	50
Pg 11	10	TNC-P110NG	TNC-P110B	18.6	13	50
Pg 11	12	TNC-P11NG	TNC-P11B	18.6	13	50
Pg 13.5	7	TNC-P137NG	TNC-P137B	20.4	13	50
Pg 13.5	10	TNC-P130NG	TNC-P130B	20.4	13	50
Pg 13.5/1	12	TNC-P132NG	TNC-P132B	20.4	13	50
Pg 13.5/2	16	TNC-P136NG	TNC-P136B	20.4	13	50
Pg 16	10	TNC-P160NG	TNC-P160B	22.5	13	50
Pg 16	12	TNC-P162NG	TNC-P162B	22.5	13	50
Pg 16	16	TNC-P16NG	TNC-P16B	22.5	13	50
Pg 16	22	TNC-P163NG	TNC-P163B	22.5	13	30
Pg 21	16	TNC-P216NG	TNC-P216B	28.3	13	30
Pg 21	22	TNC-P21NG	TNC-P21B	28.3	15	30
Pg 29	28	TNC-P29NG	TNC-P29B	37.0	15	30
Pg 36	36	TNC-P36NG	TNC-P36B	47.0	19	10
Pg 48	48	TNC-P48NG	TNC-P48B	59.3	21	10

PF Thread

Size	Suitable for Conduit Size	Cat. No. Grey	Cat. No. Black	Thread Diameter (mm)	Thread Length (mm)	Standard Pack (pieces)
G 1/4"	7	TNC-G07NG	TNC-G07B	13.0	11	50
G 1/2"	10	TNC-G10NG	TNC-G10B	20.9	13	50
G 1/2"	12	TNC-G12NG	TNC-G12B	20.9	13	50
G 1/2"	16	TNC-G16NG	TNC-G16B	20.9	13	50
G 3/4"	22	TNC-G22NG	TNC-G22B	26.4	15	30
G 1"	28	TNC-G28NG	TNC-G28B	33.2	15	30
G 1 1/4"	36	TNC-G36NG	TNC-G36B	41.9	19	10
G 1 1/2"	48	TNC-G42NG	TNC-G42B	47.8	21	10
G 2"	48	TNC-G48NG	TNC-G48B	59.6	21	10



These connectors are used to clamp flexible corrugated conduits. They offer IP67 protection and are available in Pg, Metric, PF and NPT threads.

STRAIGHT CONNECTORS (METRIC & NPT THREAD)


Technical Details :	
Material	Polyamide 6
Colour	RAL 7001 (Grey) RAL 9005 (Black)
Temperature Range	-40°C to +105°C Continuous, +150°C Short Term
Protection Class	IP 67
Threads available	Metric & NPT
Approvals	

Metric Thread

Size	Suitable for Conduit Size	Cat. No. Grey	Cat. No. Black	Thread Diameter (mm)	Thread Length (mm)	Standard Pack (pieces)
M 12 x 1.5	7	TNC-M107NG	TNC-M107B	12.0	11	50
M 12 x 1.5	10	TNC-M10NG	TNC-M10B	12.0	13	50
M 12 x 1.5	12	TNC-M102NG	TNC-M102B	12.0	13	50
M 16 x 1.5	7	TNC-M127NG	TNC-M127B	16.0	11	50
M 16 x 1.5	10	TNC-M120NG	TNC-M120B	16.0	13	50
M 16 x 1.5	12	TNC-M12NG	TNC-M12B	16.0	13	50
M 16 x 1.5	16	TNC-M126NG	TNC-M126B	16.0	13	50
M 20 x 1.5	16	TNC-M16NG	TNC-M16B	20.0	13	50
M 20 X 1.5	7	TNC-M167NG	TNC-M167B	20.0	11	50
M 20 X 1.5	10	TNC-M20NG	TNC-M20B	20.0	13	50
M 20 X 1.5	12	TNC-M202NG	TNC-M202B	20.0	13	50
M 25 x 1.5	22	TNC-M22NG	TNC-M22B	25.0	15	30
M 25 x 1.5	16	TNC-M226NG	TNC-M226B	25.0	13	30
M 32 x 1.5	22	TNC-M3222NG	TNC-M3222B	32.0	15	30
M 32 x 1.5	28	TNC-M28NG	TNC-M28B	32.0	15	30
M 40 x 1.5	28	TNC-M4028NG	TNC-M4028B	40.0	15	10
M 40 x 1.5	36	TNC-M36NG	TNC-M36B	40.0	19	10
M 50 x 1.5	36	TNC-M5036NG	TNC-M5036B	50.0	19	10
M 50 x 1.5	48	TNC-M48NG	TNC-M48B	50.0	21	10
M 63 x 1.5	48	TNC-M6348NG	TNC-M6348B	63.0	21	10

NPT Thread

Size	Suitable for Conduit Size	Cat. No. Grey	Cat. No. Black	Thread Diameter (mm)	Thread Length (mm)	Standard Pack (pieces)
NPT 1/2"	10	TNC-N10NG	TNC-N10B	21.2	13	50
NPT 1/2"	12	TNC-N12NG	TNC-N12B	21.2	13	50
NPT 1/2"	16	TNC-N16NG	TNC-N16B	21.2	13	50
NPT 3/4"	22	TNC-N22NG	TNC-N22B	26.5	15	30
NPT 1"	28	TNC-N28NG	TNC-N28B	33.2	15	30